

Specifikationer AIE MAGMAX 275

ENGINE :	Displacement 249.4cc / 4-Stroke
Cooling:	Water-Cooled
Bore and Stroke:	71 x 63 mm
Max. HP:	13.2 KW / 7000 rpm
Max. Torque:	20.6 Nm / 5500 rpm
Transmission:	Automatic CVT with Reverse Gear
Compression Ratio:	10.5 : 1
Front Suspension:	Double A-arm
Rear Suspension:	Swing Arm
BRAKES:	Front & Rear Brake / Hydraulic Disc
Foot Brake:	All Wheels Stop by Foot Pedal
Parking Brake:	Mechanical Lock of The Lever
Front Tires:	22 x 7-12 (on-road)
Rear Tires:	22 x 10-12 (on-road)
Front Rim:	Aluminum Alloy Rims 12" x 6" (ET + 15)
Rear Rim:	Aluminum Alloy Rims 12" x 7.5" (ET - 35)
Wheelbase:	1295 mm
Wheel Tread (F / R):	935mm / 895mm
Length/ Width/ Height:	2060 mm x1270 mm x 1165 mm
Seat Height:	830 mm
Dry Weight:	216 kgs

Specifikationer AIE 4-CROSS

ENGINE	Displacement 170c.c / 4-Stroke Horizontal
Cooling:	Air and Oil Cooled
Max. Torque:	12.2 Nm / 5000 rpm
Transmission:	Automatic CVT with Reverse Gear
Drive Train:	Chain
Starting:	Electric with Kick Backup
Ignition:	CDI
Front Suspension:	Double A-arm with 175 mm of Travel
Rear Suspension:	Swing Arm with 200 mm of Travel
Shock Absorber:	5-Stage Adjustable Shock
Front Brake:	130 mm Large Drum
Rear Brake:	Hydraulic Disc, Twin Piston Caliper
Parking Brake:	Mechanical Lock of Handle Lever
Front Tires:	22 x 7-10
Rear Tires:	22 x 10-10
Wheelbase:	1215 mm
Length/ Width/ Height:	1940 x 1100 x 1280 mm
Seat Height:	820 mm
Dry Weight:	162 kgs

Specifikationer Dinli 904 / Dinli 901

Total længde	1789 mm
Total bredde	1160 mm
Total højde	1214 mm
Vejafstand	285 mm
Akselafstand	1268 mm
Sæde højde	820 mm
Netto vægt	210 kg
Start System	Elektrisk
Kobling	Manual udløsning, Multi-Plade
Gear skift	R-1-N-2-3-4-5
Fordæk	22x7-10
Bagdæk	22x11-9
Forrest støddæmper	Dual A-arm, 11j ^a bevægelighed
Bagerst støddæmper	Swing Arm, 10j ^a bevægelighed
Forbremse	Dobbelt hydraulisk skive
Bagbremse	Single hydraulisk skive
Benzintank	12.8 Liter
Maximum hastighed	105 km/hr
Type	4 takt DOHC Benzin motor
Motorydelse	448 c.c.
Benzin	Blyfri, Oktan 95 eller derover
Forbrændingskammer	Halvkugleformet
Kompressionsforhold	10.8:1
Kompressionstryk	130 psi
HK. Max	33.6 kw/8250 rpm
Moment Max	41.2 N-m/7500 rpm
Tomgang	1600 rpm
Karburator	BSR42
Køling metode	Vandkølet
Smøringssystem	Bundkar
Olie pumpe type	Gear
Filter Type	Foam
Smøringolie klasse	Automobile motor olie 10w-40, Kvalitet SF eller højere
Volume	2.5 Liter
Tændingssystem	CDI
Batteri	14 Ah
Gearkasse type	5-gears, med bakgear