



**SPECIFICATIONS**

<b>Engine Type</b>	403 c.c. 4T, Single Cylinder, S.O.H.C
<b>Ignition</b>	Electric C.D.I
<b>Starter</b>	Electric/Recoil
<b>Bore x Stroke</b>	Ø 86 x 69.4 mm
<b>Compression Ratio</b>	9.2
<b>Carburetor</b>	Mikuni 36.0 mm
<b>Max Power</b>	21 kw / 7000 rpm
<b>Drive System</b>	4x4 Shaft Drive
<b>Shift Gear</b>	L/H/N/R
<b>Transmission</b>	V-belt C.V.T Automatic
<b>Front Suspension</b>	Double A-Arm
<b>Rear Suspension</b>	Swing A-Arm
<b>Front Brakes</b>	Disc
<b>Rear Brakes</b>	Disc
<b>Front Tires</b>	AT25 x 8-12
<b>Rear Tires</b>	AT25 x 10-12
<b>Wheelbase</b>	1280 mm
<b>Length/Width/Height</b>	2200/1235/1235 mm
<b>Seat Height</b>	900 mm
<b>Fuel Capacity</b>	18 L
<b>Ground Clearance</b>	305 mm
<b>Basic Weight</b>	330 kg
<b>Outlet electrical connector</b>	DC 12V 10A 120W
<b>Colors</b>	RED//BLACK//YELLOW//GRAY

